








NOZZLE
ORIENTATION




SEAMPLAN




SHELLTO
HEAD




SHELLTO
SHELL



MANHOLE
DETAIL



LIFTINGLUG



BASE&PILLAR

SPECIFICATION

1. Catpacity:1.500litres
2. Design pressure : 10 kg/cm²
3. Working pressure : 08 kg/cm²
4. Hydro test pressure : 15 kg/cm²
5. VietNamstandardcode:TCVN8366:2010

Capacity			1524lits	
WEIGHT&CAPACITY(Estimated)				
M1	1	150x190	MANHOLE	
N5	1	20A	DRAIN	
N4	1	20A	SAFETYVALVE	
N3	1	10A	PRESSUREGAUGE	
N2	1	50A	AIROUTLET	
N1	1	50A	AIRINLET	
MARK NO	NO. REQ	SIZE	DESIGNATION	REMARKS

MARK	DESCRIPTION	DIMENSION	MATERIAL	QUANTITY	REMARKS
9	GussetPlate	t5	CT3	2	
8	Buffer	t5	SyntheticRubber	1	
7	GussetPlate				
6	AnchorBoltNut	M16	SS400	3SETS	
5	LiftingLug	t8	CT3	2	
4	BasePlate	t6	SS400	3	
3	Chassis	U100x50	CT3	3	
2	Head	t8	SS400	2	2:1ELLIP
1	Shell	t8	SS400	1	

FUNCTION	NAME	SIGN	INVESTOR
DESIGNER	Ng.ThanhTuan		TITLE: AIRRECEIVERTANK1,500lits
DRAWER	Ng.ThanhTuan		DESCRIPTION: ASSEMBLY&DETAILDWG.
CHECK	DoQuocDung		
DATE	SCALE		DRAWINGNO.
032011	1:20		
	REVISION		